

SECTION 1: Identification

1.1. Product identifier

Trade name	: DIETHYL ETHER
EC-No.	: 200-467-2
EC Index-No.	: 603-022-00-4
CAS-No.	: 60-29-7
UN-No. (ADR)	: 1155
Product code	: 104050xxx
Formula	: C ₄ H ₁₀ O

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses and restrictions	: For laboratory use only
-----------------------------------	---------------------------

1.3. Supplier's details

Labchem (Pty)Ltd
 6 Wakefield Road
 Founders Hill
 1609 Johannesburg - South Africa
 T +27 11 452 1116 - F +27 86 588 0293
techlab@labchem.co.za - www.labchem.co.za

1.4. Emergency telephone number

Emergency number	: +27 11 452 1116
------------------	-------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Flammable liquids, Category 1	H224
Acute toxicity (oral), Category 4	H302
Acute toxicity (dermal) Not classified	
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment - Acute Hazard Not classified	
Full text of H statements : see section 16	

2.2. Label elements

Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA) :



GHS02

GHS07

Signal word (GHS-ZA)	: Danger
Hazard statements (GHS-ZA)	: H224 - Extremely flammable liquid and vapour. H302 - Harmful if swallowed. H336 - May cause drowsiness or dizziness.
Precautionary statements (GHS-ZA)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER or doctor if you feel unwell.

DIETHYL ETHER

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

P330 - Rinse mouth.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Extremely flammable liquid and vapour, May cause drowsiness or dizziness, Harmful if swallowed.

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance identification codes: See section 1.1

Name	Product identifier	%	Classification according to the United Nations GHS
diethyl ether (Main constituent)	(CAS-No.) 60-29-7	≥ 99.85	Flam. Liq. 1, H224 Acute Tox. 4 (Oral), H302 Acute Tox. Not classified (Dermal) STOT SE 3, H336 Aquatic Acute Not classified

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give alcohol to drink. Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Wash immediately with lots of water. Soap may be used. Take victim to a doctor if irritation persists. Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist if irritation persists. Do not apply neutralizing agents. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Call Poison Information Centre (www.big.be/antigif.html). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital. Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Paleness. Dry/sore throat. Coughing. Headache. Central nervous system depression. Dizziness. Narcosis. Mental confusion. Excited/restless. EXPOSURE TO HIGH CONCENTRATIONS: Disturbed tactile sensibility. Disturbances of consciousness. Dilation of the blood vessels. Low arterial pressure. Slowing heart action. Change in the haemogramme/blood composition. Possible laryngeal spasm/oedema. Respiratory difficulties. FOLLOWING SYMPTOMS MAY APPEAR LATER: Nausea. Vomiting. Loss of appetite.

Symptoms/effects after skin contact : ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

Symptoms/effects after eye contact : Redness of the eye tissue. Lacrimation. ON CONTINUOUS EXPOSURE/CONTACT: Irritation of the eye tissue.

Symptoms/effects after ingestion : Gastrointestinal complaints. Risk of aspiration pneumonia. Symptoms similar to those listed under inhalation. AFTER INGESTION OF HIGH QUANTITIES: Enlargement/affection of the liver. Affection of the renal tissue.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Feeling of weakness. Dry skin. Skin rash/inflammation. Possible inflammation of the respiratory tract. Headache. Impaired concentration. Dizziness. Disturbed tactile sensibility. Sleeplessness. Loss of appetite. Visual disturbances.

Potential adverse human health effects and symptoms : Harmful if swallowed. Non-toxic in contact with skin (LD50 skin > 5000 mg/kg). Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness. Moderately irritant for eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

DIETHYL ETHER

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Quick-acting ABC powder extinguisher. Quick-acting BC powder extinguisher. Quick-acting class B foam extinguisher. Quick-acting CO2 extinguisher. Class B foam (not alcohol-resistant). Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Water (quick-acting extinguisher, reel); risk of puddle expansion. Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : DIRECT FIRE HAZARD: Extremely flammable liquid and vapour. Gas/vapour flammable with air within explosion limits. INDIRECT FIRE HAZARD: May build up electrostatic charges: risk of ignition. May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard". Extremely flammable liquid and vapour.
- Explosion hazard : DIRECT EXPLOSION HAZARD: Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD: May form explosive peroxides. Heat may cause pressure rise in tanks/drums: explosion risk. may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".
- Hazardous decomposition products in case of fire : Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

- Firefighting instructions : If no hazard for/from the surroundings: controlled burning. If hazardous substances are nearby: consider extinguishment. Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.
- Protection during firefighting : Heat/fire exposure: compressed air apparatus (EN 136 + EN 137). Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.1.1. For non-emergency personnel

- Protective equipment : Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Large spills/in enclosed spaces: compressed air apparatus (EN 136 + EN 137).
- Emergency procedures : Ventilate spillage area. Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Avoid contact with air. Protect substance against light. Wash contaminated clothes. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Compressed air apparatus (EN 136 + EN 137). For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released product, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute/disperse combustible gas/vapour with water curtain. Dilute narcotic gases/vapours with water spray. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over spills.
- Methods for cleaning up : Take up liquid spill into absorbent material. Take up liquid spill into a non combustible material e.g.: sand/earth kieselguhr, powdered limestone. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

DIETHYL ETHER

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly. Work under local exhaust/ventilation. Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle and open the container with care. Cool before opening. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Keep container tightly closed. Before use: check for peroxides and eliminate them. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Observe normal hygiene standards. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Storage area : Store in a cool area. Store in a dry area. Store in a dark area. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills. Provide the tank with earthing. Store only in a limited quantity. Store only in a stabilized state. May be stored under nitrogen. Meet the legal requirements.
- Heat and ignition sources : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.
- Information on mixed storage : KEEP SUBSTANCE AWAY FROM: combustible materials. oxidizing agents. (strong) acids. halogens.
- Special rules on packaging : SPECIAL REQUIREMENTS: hermetical. clean. opaque. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
- Packaging materials : SUITABLE MATERIAL: steel. aluminium. iron. glass. tin. MATERIAL TO AVOID: zinc.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DIETHYL ETHER (60-29-7)	
South Africa - Occupational Exposure Limits (Recommended Limits)	
Local name	Diethyl ether (Ethyl ether)
OEL TWA (mg/m ³)	1200 mg/m ³
OEL TWA (ppm)	400 ppm
OEL STEL (mg/m ³)	1500 mg/m ³
OEL STEL (ppm)	500 ppm
Regulatory reference	Government Notice. R: 1179

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

- Materials for protective clothing : GIVE EXCELLENT RESISTANCE: PVA. GIVE GOOD RESISTANCE: tetrafluoroethylene. GIVE POOR RESISTANCE: butyl rubber. natural rubber. neoprene. polyethylene. PVC. viton
- Hand protection : Gloves
- Eye protection : Protective goggles (EN 166)
- Skin and body protection : Head/neck protection. Protective clothing (EN 14605 or EN 13034)
- Respiratory protection : Full face mask with filter type AX at conc. in air > exposure limit

Personal protective equipment symbol(s):



8.4. Exposure limit values for the other components

No additional information available

DIETHYL ETHER

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Molecular mass	: 74.12 g/mol
Colour	: Colourless.
Odour	: Medicinal odour.
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: 11
Relative evaporation rate (ether=1)	: 1
Melting point	: -116 °C
Freezing point	: No data available
Boiling point	: 35 °C
Flash point	: -45 °C (Weight of evidence approach)
Critical temperature	: 193 °C
Auto-ignition temperature	: 175 °C
Decomposition temperature	: > 550 °C
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 587 hPa (20 °C)
Vapour pressure at 50 °C	: 1780 hPa
Critical pressure	: 36063 hPa
Relative vapour density at 20 °C	: 2.6
Relative density	: 0.71
Relative density of saturated gas/air mixture	: 1.9
Density	: 713 kg/m ³
Relative gas density	: No data available
Solubility	: Moderately soluble in water. Substance floats in water. Soluble in ethanol. Soluble in acetone. Soluble in chloroform. Soluble in xylene. Soluble in petroleum spirit. Soluble in hydrogenchloride. Soluble in naphtha. Water: 7 g/100ml
Partition coefficient n-octanol/water (Log Pow)	: 0.82 – 0.89 (Experimental value)
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 0.337 mm ² /s
Viscosity, dynamic	: 0.24 mPa·s (20 °C)
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 2 – 48 vol %
Lower explosive limit (LEL)	: 2 vol %
Upper explosive limit (UEL)	: 48 vol %

9.2. Other information

Minimum ignition energy	: 0.19 mJ
Specific conductivity	: 30 pS/m
Saturation concentration	: 1776 g/m ³
VOC content	: 100 %
Other properties	: Gas/vapour heavier than air at 20°C. Clear. Highly volatile. Neutral reaction. May generate electrostatic charges.

SECTION 10: Stability and reactivity

10.1. Reactivity

On exposure to air: peroxidation resulting in increased fire or explosion risk. This reaction is accelerated on exposure to light and on exposure to impurities. Reacts violently with many compounds e.g.: with (strong) oxidizers and with (some) halogens: heat release resulting in increased fire or explosion risk. Reacts violently with sulphurized compounds. Extremely flammable liquid and vapour.

10.2. Chemical stability

Unstable on exposure to light. Unstable on exposure to air.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

DIETHYL ETHER

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified

DIETHYL ETHER (60-29-7)	
LD50 oral rat	1200 – 1700 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Oral, 7 day(s))
LD50 dermal rabbit	> 14200 mg/kg (Rabbit, Dermal)
LC50 inhalation rat (mg/l)	99 mg/l (4 h, Rat, Inhalation)
LC50 inhalation rat (ppm)	32 000 ppm (4 h, Rat, Inhalation)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

DIETHYL ETHER (60-29-7)	
Viscosity, kinematic	0.337 mm ² /s

Potential adverse human health effects and symptoms : Harmful if swallowed. Non-toxic in contact with skin (LD50 skin > 5000 mg/kg). Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness. Moderately irritant for eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Not classified as dangerous for the environment according to the criteria of Directive 67/548/EEC. Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.
Ecology - air : Not included in the list of substances which may contribute to the greenhouse effect (IPCC). Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014). Reacts with air. Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).
Ecology - water : Not harmful to crustacea. Not harmful to fishes.
Hazardous to the aquatic environment, short-term (acute) : Not classified.
Hazardous to the aquatic environment, long-term (chronic) : Not classified

DIETHYL ETHER (60-29-7)	
LC50 fish 1	2560 mg/l (96 h, Pimephales promelas, Flow-through system)
EC50 Daphnia 1	1380 mg/l (48 h, Daphnia magna)
BCF fish 1	0.9 – 9.1 (Cyprinus carpio, Test duration: 6 weeks)
Partition coefficient n-octanol/water (Log Pow)	0.82 – 0.89 (Experimental value)

12.2. Persistence and degradability

DIETHYL ETHER (60-29-7)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.03 g O ₂ /g substance
Chemical oxygen demand (COD)	0.026 g O ₂ /g substance (KMnO ₄)
ThOD	2.6 g O ₂ /g substance
BOD (% of ThOD)	0.012

DIETHYL ETHER

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

12.3. Bioaccumulative potential

DIETHYL ETHER (60-29-7)	
BCF fish 1	0.9 – 9.1 (Cyprinus carpio, Test duration: 6 weeks)
Partition coefficient n-octanol/water (Log Pow)	0.82 – 0.89 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

DIETHYL ETHER (60-29-7)	
Mobility in soil	No additional information available
Surface tension	0.017 N/m (20 °C)
Partition coefficient n-octanol/water (Log Pow)	0.82 – 0.89 (Experimental value)
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available




SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Do not discharge into surface water. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle by distillation. Incinerate under surveillance with energy recovery.
Additional information	: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
14.1. UN number		
1155	1155	1155
14.2. Proper Shipping Name		
DIETHYL ETHER (ETHYL ETHER)	DIETHYL ETHER (ETHYL ETHER)	Diethyl ether
14.3. Transport hazard class(es)		
3	3	3
		 Not applicable
14.4. Packing group		
I	I	I
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
	:	
No supplementary information available		

14.6. Special precautions for user

- SANS

Transport regulations (UN)	: Subject to the provisions
Limited quantities (SANS)	: 0
Limited quantities (SANS)	: 0
Packagings, large packagings and IBCs	: P001
Packing instructions (SANS)	
Portable tank and bulk containers instructions (SANS)	: T11

DIETHYL ETHER

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Portable tank and bulk container special provisions (SANS) : TP2

- IMDG

Transport regulations (IMDG) : Subject to the provisions
Limited quantities (IMDG) : 0
Excepted quantities (IMDG) : E3
Packing instructions (IMDG) : P001
Tank instructions (IMDG) : T11
Tank special provisions (IMDG) : TP2
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : E
Flash point (IMDG) : -40°C c.c.
Properties and observations (IMDG) : Colourless, volatile and mobile liquid with a pleasant aromatic odour. Flashpoint: -40°C c.c. Explosive limits: 1.7% to 48%. Boiling point: 34°C. Immiscible with water. In the presence of oxygen or on long standing or exposure to sunlight, unstable peroxides sometimes form; these may explode spontaneously or when heated. Strongly narcotic. Readily ignited by static electricity.

- IATA

Transport regulations (IATA) : Subject to the provisions
PCA Excepted quantities (IATA) : E3
PCA Limited quantities (IATA) : Forbidden
PCA limited quantity max net quantity (IATA) : Forbidden
PCA packing instructions (IATA) : 351
PCA max net quantity (IATA) : 1L
CAO packing instructions (IATA) : 361
CAO max net quantity (IATA) : 30L
ERG code (IATA) : 3AH

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

Regulatory reference : SANS 10234:2008; SANS 11014:2010; SANS 10228:2012; SANS 10229:2010; SANS 10232(1,2,4), SANS 10231:2018; Occupational Health and Safety Act 85 of 1993; National Road Traffic Act 93 of 1996.

SECTION 16: Other information

Issue date : 22/01/2020
Revision date : 22/01/2025

Full text of H-statements:

H224	Extremely flammable liquid and vapour.
H302	Harmful if swallowed.
H336	May cause drowsiness or dizziness.

SDS South Africa

The data provided in this Safety Data Sheet (SDS) is correct to the best of our knowledge. The data relates to the specific product as named and is intended as a guide to the safe handling of the product in all its facets. The data may no longer be valid if the product is used in any process or in combination with other products. This SDS is not a quality specification nor any form of guarantee.