

SECTION 1: Identification

1.1. Product identifier

Trade name : HEXANES
 EC-No. : 203-777-6
 EC Index-No. : 601-037-00-0
 CAS-No. : 110-54-3
 UN-No. (ADR) : 1208
 Product code : 108030xxx
 Formula : C₆H₁₄

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses and restrictions : For laboratory use only

1.3. Supplier's details

Labchem (Pty)Ltd
 6 Wakefield Road
 Founders Hill
 1609 Johannesburg - South Africa
 T +27 11 452 1116 - F +27 86 588 0293
techlab@labchem.co.za - www.labchem.co.za

1.4. Emergency telephone number

Emergency number : +27 11 452 1116

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Flammable liquids, Category 2 H225
 Acute toxicity (oral) Not classified
 Skin corrosion/irritation, Category 2 H315
 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
 Specific target organ toxicity — Repeated exposure, Category 2 H373
 Aspiration hazard, Category 1 H304
 Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
 Full text of H statements : see section 16

2.2. Label elements

Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA) :



Signal word (GHS-ZA) : Danger

Hazard statements (GHS-ZA) :

- H225 - Highly flammable liquid and vapour.
- H304 - May be fatal if swallowed and enters airways.
- H315 - Causes skin irritation.
- H336 - May cause drowsiness or dizziness.
- H373 - May cause damage to organs through prolonged or repeated exposure.
- H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (GHS-ZA) :

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 - Keep container tightly closed.
- P240 - Ground and bond container and receiving equipment.
- P241 - Use explosion-proof equipment.
- P242 - Use non-sparking tools.
- P243 - Take action to prevent static discharges.
- P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 - Wash hands, forearms and face thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.

HEXANES

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Highly flammable liquid and vapour, May cause damage to organs through prolonged or repeated exposure, May cause drowsiness or dizziness, Causes skin irritation, May be fatal if swallowed and enters airways, Toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance identification codes: See section 1.1

Name	Product identifier	%	Classification according to the United Nations GHS
hexanes, mixture of isomers (Main constituent)	(CAS-No.) 110-54-3	≥ 90	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give alcohol to drink. Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Wash immediately with lots of water. Soap may be used. Take victim to a doctor if irritation persists. Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist if irritation persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth with water. Do not induce vomiting. Give activated charcoal. Call Poison Information Centre (www.big.be/antigif.html). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital. Doctor: gastric lavage. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : EXPOSURE TO HIGH CONCENTRATIONS: Central nervous system depression. Dizziness. Narcosis. Drunkenness. Headache. Nausea. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Disturbances of consciousness.

Symptoms/effects after skin contact : Tingling/irritation of the skin. Irritation.

Symptoms/effects after eye contact : No effects known.

HEXANES

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Symptoms/effects after ingestion	: Vomiting. Risk of aspiration pneumonia. Nausea. Symptoms similar to those listed under inhalation. Risk of lung oedema.
Chronic symptoms	: Feeling of weakness. Loss of weight. Dry skin. Disturbed tactile sensibility. Movement disturbances. Myasthenia. Cramps/uncontrolled muscular contractions. Paralysis. Gastrointestinal complaints. Loss of appetite. Visual disturbances.
Potential adverse human health effects and symptoms	: Odour threshold is well above the exposure limit. Non-toxic if swallowed (LD50 oral, rat > 5000 mg/kg). May be fatal if swallowed and enters airways. Causes skin irritation. Slightly irritant to skin. Practically non-toxic in contact with skin (LD50 skin > 2000 mg/kg). May cause drowsiness or dizziness. Slightly harmful by inhalation. Not irritant to eyes. Caution! Substance is absorbed through the skin.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Quick-acting ABC powder extinguisher. Quick-acting BC powder extinguisher. Quick-acting class B foam extinguisher. Quick-acting CO2 extinguisher. Class B foam (not alcohol-resistant). Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Water (quick-acting extinguisher, reel); risk of puddle expansion. Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: DIRECT FIRE HAZARD: Highly flammable liquid and vapour. Gas/vapour flammable with air within explosion limits. INDIRECT FIRE HAZARD: May build up electrostatic charges: risk of ignition. May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard". Highly flammable liquid and vapour.
Explosion hazard	: DIRECT EXPLOSION HAZARD: Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD: may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".
Hazardous decomposition products in case of fire	: Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions	: Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.
Protection during firefighting	: Heat/fire exposure: compressed air apparatus (EN 136 + EN 137). Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.1.1. For non-emergency personnel

Protective equipment	: Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Large spills/in enclosed spaces: compressed air apparatus (EN 136 + EN 137). Large spills/in enclosed spaces: gas-tight suit (EN 943).
Emergency procedures	: Ventilate spillage area. Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Keep containers closed. Wash contaminated clothes. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

For containment	: Contain released product, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute/disperse combustible gas/vapour with water curtain. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over spills. Collect spillage.
-----------------	--

HEXANES

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

- Methods for cleaning up : Take up liquid spill into absorbent material. Liquid spill: dam up with sand/earth. Take up liquid spill into a non combustible material e.g.: sand/earth or kieselguhr. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly. Work under local exhaust/ventilation. Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Observe strict hygiene. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Storage area : Store in a cool area. Ventilation at floor level. Fireproof storeroom. Provide for a tub to collect spills. Provide the tank with earthing. Meet the legal requirements.
- Heat and ignition sources : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.
- Information on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents.
- Special rules on packaging : SPECIAL REQUIREMENTS: closing. clean. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
- Packaging materials : SUITABLE MATERIAL: steel. stainless steel. aluminium. iron. copper. bronze. polyethylene. polypropylene. glass.
- Storage temperature : 20 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HEXANES (110-54-3)	
South Africa - Occupational Exposure Limits (Recommended Limits)	
Local name	n-Hexane
OEL TWA (mg/m ³)	70 mg/m ³
OEL TWA (ppm)	20 ppm
Regulatory reference	Government Notice. R: 1179

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

- Materials for protective clothing : GIVE EXCELLENT RESISTANCE: nitrile rubber. PVA. tetrafluoroethylene. viton. GIVE POOR RESISTANCE: butyl rubber. natural rubber. neoprene. polyethylene. PVC. styrene-butadiene rubber
- Hand protection : Gloves
- Eye protection : Protective goggles (EN 166)
- Skin and body protection : Head/neck protection. Protective clothing (EN 14605 or EN 13034)
- Respiratory protection : Full face mask with filter type A at conc. in air > exposure limit

Personal protective equipment symbol(s):

HEXANES

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 86.18 g/mol
Colour	: Colourless.
Odour	: Petroleum-like odour. Mild odour.
Odour threshold	: No data available
pH	: 7 (0.01 g/l, 25 °C)
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: > 10
Relative evaporation rate (ether=1)	: 1.3
Melting point	: -95 °C (1013 hPa)
Freezing point	: No data available
Boiling point	: 69 °C (1013 hPa)
Flash point	: -22 °C (1013 hPa)
Critical temperature	: 234 °C
Auto-ignition temperature	: 280 °C (1013 hPa)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 100 hPa (9.8 °C)
Vapour pressure at 50 °C	: No data available
Critical pressure	: 30120 hPa
Relative vapour density at 20 °C	: 2.97
Relative density	: 0.66 (25 °C)
Relative density of saturated gas/air mixture	: 1.3
Density	: 660 kg/m ³ (25 °C)
Relative gas density	: No data available
Solubility	: Insoluble in water. Substance floats in water. Soluble in ethanol. Soluble in ether. Soluble in acetone. Soluble in chloroform. Soluble in oils/fats. Water: < 0.01 g/100ml (insoluble) Ethanol: soluble Ether: soluble Acetone: soluble
Partition coefficient n-octanol/water (Log Pow)	: 4 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 0.455 mm ² /s (20 °C)
Viscosity, dynamic	: 0.3 mPa·s (25 °C)
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1.1 – 7.5 vol %
Lower explosive limit (LEL)	: 1.1 vol %
Upper explosive limit (UEL)	: 7.5 vol %

9.2. Other information

Minimum ignition energy	: 0.24 mJ
Specific conductivity	: 0.00001 pS/m
Saturation concentration	: 566 g/m ³
VOC content	: 100 %
Other properties	: Gas/vapour heavier than air at 20°C. Clear. Volatile. Neutral reaction. May generate electrostatic charges.

HEXANES

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with (strong) oxidizers: (increased) risk of fire/explosion. Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

HEXANES (110-54-3)	
LD50 oral rat	16000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 3350 mg/kg bodyweight (Equivalent or similar to OECD 402, 4 h, Rabbit, Male, Read-across, Dermal)
LC50 inhalation rat (ppm)	> 5000 ppm (Equivalent or similar to OECD 403, 24 h, Rat, Male, Experimental value, Inhalation (vapours))

Skin corrosion/irritation : Causes skin irritation.
pH: 7 (0.01 g/l, 25 °C)

Serious eye damage/irritation : Not classified
pH: 7 (0.01 g/l, 25 °C)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

HEXANES (110-54-3)	
Viscosity, kinematic	0.455 mm ² /s (20 °C)

Potential adverse human health effects and symptoms : Odour threshold is well above the exposure limit. Non-toxic if swallowed (LD50 oral, rat > 5000 mg/kg). May be fatal if swallowed and enters airways. Causes skin irritation. Slightly irritant to skin. Practically non-toxic in contact with skin (LD50 skin > 2000 mg/kg). May cause drowsiness or dizziness. Slightly harmful by inhalation. Not irritant to eyes. Caution! Substance is absorbed through the skin.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Dangerous for the environment. Toxic to aquatic life with long lasting effects.

Ecology - air : Not included in the list of substances which may contribute to the greenhouse effect (IPCC). Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014). Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).

Ecology - water : Harmful to crustacea. Harmful to fishes. Fouling to shoreline. Toxic to algae. Photooxidation in water.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

HEXANES

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

HEXANES (110-54-3)	
BCF fish 1	501.187 (Other, Pimephales promelas, QSAR)
Partition coefficient n-octanol/water (Log Pow)	4 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Partition coefficient n-octanol/water (Log Koc)	3.34 (log Koc, QSAR)

12.2. Persistence and degradability

HEXANES (110-54-3)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
ThOD	3.52 g O ₂ /g substance

12.3. Bioaccumulative potential

HEXANES (110-54-3)	
BCF fish 1	501.187 (Other, Pimephales promelas, QSAR)
Partition coefficient n-octanol/water (Log Pow)	4 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Partition coefficient n-octanol/water (Log Koc)	3.34 (log Koc, QSAR)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

12.4. Mobility in soil

HEXANES (110-54-3)	
Mobility in soil	No additional information available
Surface tension	0.018 N/m (25 °C, 1 g/l)
Partition coefficient n-octanol/water (Log Pow)	4 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Partition coefficient n-octanol/water (Log Koc)	3.34 (log Koc, QSAR)
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Do not discharge into surface water. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle by distillation. Incinerate under surveillance with energy recovery. Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.
Additional information	: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
14.1. UN number		
1208	1208	1208
14.2. Proper Shipping Name		
HEXANES	HEXANES	Hexanes
14.3. Transport hazard class(es)		
3	3	3
		 Not applicable
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment : Yes	Dangerous for the environment : No :	Dangerous for the environment : No

HEXANES

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SANS	IMDG	IATA
No supplementary information available		

14.6. Special precautions for user

- SANS

Transport regulations (UN)	: Subject to the provisions
Limited quantities (SANS)	: 1 L
Limited quantities (SANS)	: 1 L
Packagings, large packagings and IBCs	: P001, IBC02
Packing instructions (SANS)	
Portable tank and bulk containers instructions (SANS)	: T4
Portable tank and bulk container special provisions (SANS)	: TP1

- IMDG

Transport regulations (IMDG)	: Subject to the provisions
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP2
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: E
Properties and observations (IMDG)	: Colourless, volatile liquids with a faint odour. Explosive limits: 1.1% to 7.5% n-HEXANE: flashpoint -22°C c.c. boiling point 69°C. NEOHEXANE: flashpoint -48°C c.c. boiling point 50°C. Immiscible with water. Slightly irritating to skin, eyes and mucous membranes.

- IATA

Transport regulations (IATA)	: Subject to the provisions
PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
ERG code (IATA)	: 3H

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

Regulatory reference	: SANS 10234:2008; SANS 11014:2010; SANS 10228:2012; SANS 10229:2010; SANS 10232(1,2,4), SANS 10231:2018; Occupational Health and Safety Act 85 of 1993; National Road Traffic Act 93 of 1996.
----------------------	--

SECTION 16: Other information

Issue date	: 13/02/2020
Revision date	: 13/02/2025

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

HEXANES

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

The data provided in this Safety Data Sheet (SDS) is correct to the best of our knowledge. The data relates to the specific product as named and is intended as a guide to the safe handling of the product in all its facets. The data may no longer be valid if the product is used in any process or in combination with other products. This SDS is not a quality specification nor any form of guarantee.