

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Trade name : ETHYL ALCOHOL DENATURED
 UN-No. (ADR) : 1170
 Product code : 113180xxx, 105130xxx

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses and restrictions : For laboratory use only

1.3. Supplier's details

Labchem (Pty)Ltd
 6 Wakefield Road
 Founders Hill
 1609 Johannesburg - South Africa
 T +27 11 452 1116 - F +27 86 588 0293
techlab@labchem.co.za - www.labchem.co.za

1.4. Emergency telephone number

Emergency number : +27 11 452 1116

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Flammable liquids, Category 2 H225

Full text of H statements : see section 16

2.2. Label elements

Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA) :



GHS02

Signal word (GHS-ZA) : Danger
 Hazard statements (GHS-ZA) : H225 - Highly flammable liquid and vapour.
 Precautionary statements (GHS-ZA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground and bond container and receiving equipment.
 P241 - Use explosion-proof equipment.
 P242 - Use non-sparking tools.
 P243 - Take action to prevent static discharges.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P370+P378 - In case of fire: Use media other than water to extinguish.
 P403+P235 - Store in a well-ventilated place. Keep cool.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Highly flammable liquid and vapour.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

ETHYL ALCOHOL DENATURED

Safety Data Sheet

According to SANS 10234:2019 and SANS 11014:2010

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
ethanol	(CAS-No.) 64-17-5	96	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Aquatic Acute Not classified
2-propanol	(CAS-No.) 67-63-0	4	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) STOT SE 3, H336 Aquatic Acute Not classified

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

ETHYL ALCOHOL DENATURED

Safety Data Sheet

According to SANS 10234:2019 and SANS 11014:2010

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ETHYL ALCOHOL DENATURED	
South Africa - Occupational Exposure Limits (Recommended Limits)	
Local name	Ethanol (Ethyl alcohol)
OEL TWA (mg/m ³)	1900 mg/m ³
OEL TWA (ppm)	1000 ppm
Regulatory reference	Government Notice. R: 1179
2-propanol (67-63-0)	
South Africa - Occupational Exposure Limits (Recommended Limits)	
Local name	Propan-2-ol (Isopropyl alcohol)
OEL TWA (mg/m ³)	960 mg/m ³ Isopropyl alcohol 980 mg/m ³ Propan-2-ol
OEL TWA (ppm)	400 ppm
OEL STEL (mg/m ³)	1225 mg/m ³
OEL STEL (ppm)	500 ppm
Remark	Sk
Regulatory reference	Government Notice. R: 1179
ethanol (64-17-5)	
South Africa - Occupational Exposure Limits (Recommended Limits)	
Local name	Ethanol (Ethyl alcohol)
OEL TWA (mg/m ³)	1900 mg/m ³
OEL TWA (ppm)	1000 ppm
Regulatory reference	Government Notice. R: 1179

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : No data available
Colour : No data available
Odour : No data available
Odour threshold : No data available
pH : No data available
pH solution : No data available
Relative evaporation rate (butylacetate=1) : No data available
Relative evaporation rate (ether=1) : No data available
Melting point : Not applicable

ETHYL ALCOHOL DENATURED

Safety Data Sheet

According to SANS 10234:2019 and SANS 11014:2010

Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosive limit (LEL)	: No data available
Upper explosive limit (UEL)	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2-propanol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	16400 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg bodyweight (Rabbit, Experimental value, Dermal)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified

ETHYL ALCOHOL DENATURED

Safety Data Sheet

According to SANS 10234:2019 and SANS 11014:2010

Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

2-propanol (67-63-0)	
LC50 fish 1	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Partition coefficient n-octanol/water (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

ethanol (64-17-5)	
LC50 fish 1	15300 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 72h algae (1)	275 mg/l (Equivalent or similar to OECD 201, Chlorella vulgaris, Static system, Fresh water, Experimental value, Growth rate)
BCF fish 1	1 (Other, 72 h, Cyprinus carpio, Static system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	-0.31 (Experimental value)
Partition coefficient n-octanol/water (Log Koc)	0.2 (log Koc, Experimental value)

12.2. Persistence and degradability

ETHYL ALCOHOL DENATURED	
Persistence and degradability	No additional information available

2-propanol (67-63-0)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance

ethanol (64-17-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 – 0.967 g O ₂ /g substance
Chemical oxygen demand (COD)	1.7 g O ₂ /g substance
ThOD	2.1 g O ₂ /g substance
BOD (% of ThOD)	0.43

12.3. Bioaccumulative potential

ETHYL ALCOHOL DENATURED	
Bioaccumulative potential	No additional information available

2-propanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Partition coefficient n-octanol/water (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

ethanol (64-17-5)	
BCF fish 1	1 (Other, 72 h, Cyprinus carpio, Static system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	-0.31 (Experimental value)
Partition coefficient n-octanol/water (Log Koc)	0.2 (log Koc, Experimental value)
Bioaccumulative potential	Not bioaccumulative.

ETHYL ALCOHOL DENATURED

Safety Data Sheet

According to SANS 10234:2019 and SANS 11014:2010

12.4. Mobility in soil

ETHYL ALCOHOL DENATURED	
Mobility in soil	No additional information available
2-propanol (67-63-0)	
Surface tension	0.021 N/m (25 °C)
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Partition coefficient n-octanol/water (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
ethanol (64-17-5)	
Surface tension	22.31 mN/m (20 °C, 100 %)
Partition coefficient n-octanol/water (Log Pow)	-0.31 (Experimental value)
Partition coefficient n-octanol/water (Log Koc)	0.2 (log Koc, Experimental value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available




SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
14.1. UN number		
1170	1170	1170
14.2. Proper Shipping Name		
ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	Ethanol solution
14.3. Transport hazard class(es)		
3	3	3
		 Not applicable
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available		

14.6. Special precautions for user

- SANS

Special provisions (SANS)	: 144
Limited quantities (SANS)	: 1 L
Limited quantities (SANS)	: 1 L
Packagings, large packagings and IBCs	: P001, IBC02
Packing instructions (SANS)	
Portable tank and bulk containers instructions (SANS)	: T4
Portable tank and bulk container special provisions (SANS)	: TP1

- IMDG

Special provisions (IMDG)	: 144
Limited quantities (IMDG)	: 1 L

ETHYL ALCOHOL DENATURED

Safety Data Sheet

According to SANS 10234:2019 and SANS 11014:2010

Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Colourless, volatile liquids.Pure ETHANOL: flashpoint 13°C c.c. Explosive limits: 3.3% to 19% Miscible with water.

- IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A58, A180
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

Regulatory reference : SANS 10234:2008; SANS 11014:2010; SANS 10228:2012;SANS 10229:2010; SANS 10232(1,2,4), SANS 10231:2018; Occupational Health and Safety Act 85 of 1993; National Road Traffic Act 93 of 1996.

SECTION 16: Other information

Issue date : 13/07/2020
Revision date : 13/07/2025

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

SDS South Africa

The data provided in this Safety Data Sheet (SDS) is correct to the best of our knowledge. The data relates to the specific product as named and is intended as a guide to the safe handling of the product in all its facets. The data may no longer be valid if the product is used in any process or in combination with other products. This SDS is not a quality specification nor any form of guarantee.